

PARAFLU 11 Cod. 1655

DESCRIPTION

Paraflu 11 is a concentrated Ethylene Glycol protective fluid for radiators. It is suitable for professional use. Paraflu 11 provides ideal protection for the cooling systems of cars, light and heavy commercial vehicles, tractors and earth-moving machinery.

CHARACTERISTICS

The fruit of state-of-the-art experimentation at PLI research labs, the fluid responds fully to every prerequisite even in the severest operating conditions. PARAFLU 11 mixed with 50% water allows:

- Optimal removal of heat from the engine combustion chamber.
- Maximum protection against:
- freezing (down to an outside temperature of -40° C)
- the formation of scaling;
- boiling in the summer months, in motorway pileups, in city traffic (circuit temperature up to +125°C);
- corrosion of the metal elements in the cooling circuits (cast iron, aluminium, copper);
- over-bulking of the rubber and plastic elements in the circuit.



ADVICE ON USE

As recommended by the manufacturer:
total change every 2 years or every 60,000 Km
top-ups mixing the fluid with 50% water
Do not use the fluid concentrated
Do not mix fluids of different origins or makes

RECOMMENDED BY

Fiat, Lancia, Maserati, Iveco.

TECHNICAL DATA

FIAT 9.55523,
IVECO 18-1830, CONTRACTUAL TECHNICAL REF. N°I002.C00,
CUNA NC 956-16, ASTM D 3306 Type 1,
ASTM D 6210 Type 1-FF, CHRYSLER MS 7170